

Home Video Intercom

IVR 7 ID

The IVR 7 ID Video Intercom is the perfect combination of practicality, design and technology. It allows access to the place through Tag, has a practical installation and offers a quality visual experience on a 7" display.

- » Access via Tag;
- » 7" display;
- » Powered by the internal module;
- » Opening of up to 2 locks;
- » Viewing of an extra analog camera



Technical Specifications

Internal Module

Display technology	TFT — LCD
Screen size	7"
Screen format	16:9
Resolution (H x V)	800 (H) x 480 (V) RGB
Contrast	400:1
Brightness	200 cd / m²
Angle of view	70°
Dimensions (W x H x D)	24.4 x 19.1 x 6.1 cm
Operating tension	Mains 100 to 240 Vac (automatic)
Frequency of operation	50/60 Hz
Maximum consumption	< 9 W (in use) < 3 W (standby)
Weight	535 g
Operating temperature	-10 °C to 50 °C
Actuation of NO-C relay	24 V/1 A

External Module

Pinhole camera	1/4"
Lens	3.7 mm
Horizontal resolution	580 lines
Camera aperture angle	92° diagonal
Minimum illumination - Color mode	1.5 lux
Minimum illumination - B&W mode	0.2 lux
Infrared LEDs	2
RFid - MIFARE	13.56 MHz
Tamper - tamper-proof system	Yes
Material used	ABS
Electric lock opening	12 V/1 A
Dimensions (W x H x D)	10.9x 16.7 x 5.3 cm
Weight	218 g
Operating temperature	-10 °C to 50 °C
Protection rating	IP44
Frequency	433.92 MHz
Modulation	FSK (128 bits Intelbras AES Cryptography) OOK (Code Learning -Open Source)
RF Range	15 meters without obstacles

Main functions



Easy installation through internal module power supply, which facilitates installation in outdoor areas with no power input.



A new concept of external module design that brings together technology, practicality and security for different residential and commercial projects.



Everyday **practicality** with Tag access. Just bring it close to the external module, wait for the door to open and enter.



Get even more security at your front door by integrating the **display of 1 extra analog camera** and view it all on your 7" monitor.