



**4G Cellular Interface with Wi-Fi ICW 4002**

- » Web interface for configuration and management of the product.
- » Wi-Fi operates on 2.4 GHz.
- » Shares Wi-Fi internet with up to 32 devices.
- » VoLTE technology. Make voice calls over the 4G network with faster and better quality connections<sup>1</sup>.
- » SIM Card slot.
- » 1 LAN port, 1 WAN / LAN port and 1 phone connection (corded or wireless phone).
- » It comes fully configured. Simply insert an enabled SIM Card into the ICW 4002 and the product will be ready for use.

<sup>1</sup> Check availability with your operator.



The 4G Cellular Interface with Wi-Fi ICW 4002 is a device that integrates mobile and fixed telephony, developed to facilitate the sharing of the cellular line, connecting it on analog phones. Through it, it is possible to use the advantages of differentiated tariff plans offered by mobile operators with the same comfort and convenience of a fixed telephone connection, in addition to sharing the internet through the Wi-Fi. This equipment has a 2G / 3G / 4G and SIM Card adapter, included for inserting the enabled chip.

**Technical specifications**

|                         |                              |
|-------------------------|------------------------------|
| Operating temperature   | 0 °C a 45 °C                 |
| Operating frequencies   | 2G: 850/900/1800/1900 MHz    |
|                         | 3G: 850/2100 MHz             |
|                         | 4G: 700/850/1800/2600 MHz    |
| Voltage adapter         | Input: 100/240 V ~ 50-60 Hz  |
|                         | Output: 12 Vdc – 1 A         |
| Energy consumption      | At rest: approx. 2,76W       |
|                         | In operation: approx. 3,68 W |
| Antennas                | Gain: 3 dBi                  |
|                         | Impedance: 50 ohms           |
|                         | Connection: SMA fêmea        |
| FXS interface impedance | 600Ω                         |
| Dimensions (W x H x D)  | 118 x 215 x 50 mm            |

|                          |                               |                             |
|--------------------------|-------------------------------|-----------------------------|
| Wi-Fi                    | IEEE 802.11 b/g/n (20/40 MHz) |                             |
| Internet Protocol        | IPv4/IPv6                     |                             |
| Maximum connection speed | LTE-FDD                       | 150 Mbps DL / 50 Mbps UL    |
|                          | LTE-TDD                       | 112 Mbps DL / 10 Mbps UL    |
|                          | DC-HSPA+                      | 42 Mbps DL                  |
|                          | HSPA+                         | 21 Mbps DL                  |
|                          | HSPA                          | 14,4 Mbps DL / 5,76 Mbps UL |
|                          | UMTS                          | 384 kbps DL / 384 kbps UL   |
|                          | EDGE                          | 237 kbps DL / 237 kbps UL   |
|                          | GPRS                          | 85.6 kbps DL / 85.6 kbps UL |

## Application scenario

